

Tailgate/Toolbox Safety Training

SAM	

Being crushed between the vehicle and another surface	cles around a workplace. Although they are very useful equipment, to improper, careless operation. ay be referred to as: Forklifts, high-lift trucks, fork trucks, low-lift nat because of unsafe forklift operations, more than 100 people are auses for fatal or serious forklift accidents: Being hit by falling material from a dropped load Falling from a platform on the forks Running the forklift off a loading dock, ramp, or other surface w mishaps. All drivers must complete training and be evaluated before e-evaluated every 3 years. Re-training can be triggered by having an evations of unsafe operation. All employers must certify that each of careful, safe manner. The loaded or empty terial as needed. The falling loads.
Introduction: In one form or another, forklifts are one of the most common vehiforklifts are guilty of being involved in many serious injury accidents, mostly due OSHA Requirements — cover regulations for equipment of this type. Vehicles in trucks, cantilever trucks, motorized hand/rider trucks, and etc. OSHA estimates takilled, and nearly 95,000 are seriously injured every year. These are the primary of Vehicle tip-overs Obeyone Being crushed between the vehicle and another surface Obeting struck by the vehicle Getting struck by the vehicle These accidents are caused by operator errors. Well trained drivers have very fetchey're allowed to operate a fork-truck without direct supervision. They must be accident, near misses, re-assignment to different equipment or workplace, or obse his operators has been properly trained and is competent to operate the forklift in a Basic Forklift Operations: Do not allow anybody underneath raised forks, regardless whether forks at Handle only loads that are stable and safely arranged; secure palletized material Do not thandle loads in excess of the truck's or any attached component's in Always place forks under the load as far as possible when lifting; then statent Do not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar watch where you are going and keep a clear view. If the load obstructs you have divine up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stoppin when approaching or crossing obstructed visio	cles around a workplace. Although they are very useful equipment, to improper, careless operation. ay be referred to as: Forklifts, high-lift trucks, fork trucks, low-lift nat because of unsafe forklift operations, more than 100 people are auses for fatal or serious forklift accidents: Being hit by falling material from a dropped load Falling from a platform on the forks Running the forklift off a loading dock, ramp, or other surface we mishaps. All drivers must complete training and be evaluated before e-evaluated every 3 years. Re-training can be triggered by having an evations of unsafe operation. All employers must certify that each of a careful, safe manner. The loaded or empty terial as needed. The loaded of the mast. Falling loads.
forklifts are guilty of being involved in many serious injury accidents, mostly due OSHA Requirements — cover regulations for equipment of this type. Vehicles no trucks, cantilever trucks, motorized hand/rider trucks, and etc. OSHA estimates to killed, and nearly 95,000 are seriously injured every year. These are the primary of the Vehicle tip-overs Define grushed between the vehicle and another surface Getting struck by the vehicle These accidents are caused by operator errors. Well trained drivers have very feathey're allowed to operate a fork-truck without direct supervision. They must be accident, near misses, re-assignment to different equipment or workplace, or obse his operators has been properly trained and is competent to operate the forklift in a Basic Forklift Operations: Do not allow anybody underneath raised forks, regardless whether forks and Handle only loads that are stable and safely arranged; secure palletized mandle on the handle loads in excess of the truck's or any attached component's and Always place forks under the load as far as possible when lifting; then stated to not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar when where you are going and keep a clear view. If the load obstructs you never drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stoppin when approaching or crossing obstructed vision locations, or blind spots. Be sure of sufficient clearances to overhead obstructions such as lighting in Stay	to improper, careless operation. ay be referred to as: Forklifts, high-lift trucks, fork trucks, low-lift nat because of unsafe forklift operations, more than 100 people are auses for fatal or serious forklift accidents: Being hit by falling material from a dropped load Falling from a platform on the forks Running the forklift off a loading dock, ramp, or other surface w mishaps. All drivers must complete training and be evaluated before e-evaluated every 3 years. Re-training can be triggered by having an vations of unsafe operation. All employers must certify that each of careful, safe manner. The loaded or empty terial as needed. The loaded of the mast. Falling loads.
trucks, cantilever trucks, motorized hand/rider trucks, and etc. OSHA estimates to killed, and nearly 95.000 are seriously injured every year. These are the primary of the Vehicle tip-overs Desing crushed between the vehicle and another surface Desting struck by the vehicle These accidents are caused by operator errors. Well trained drivers have very fethey re allowed to operate a fork-truck without direct supervision. They must be accident, near misses, re-assignment to different equipment or workplace, or obse his operators has been properly trained and is competent to operate the forklift in a Basic Forklift Operations: Do not allow anybody underneath raised forks, regardless whether forks and Handle only loads that are stable and safely arranged; secure palletized made in Do not handle loads in excess of the truck's or any attached component's and Always place forks under the load as far as possible when lifting; then stated in Do not till mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar watch where you are going and keep a clear view. If the load obstructs you hever drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stopping. When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for Stay within rated capacities of dock boards, bridge plates, or any other elections.	nat because of unsafe forklift operations, more than 100 people are auses for fatal or serious forklift accidents: Being hit by falling material from a dropped load Falling from a platform on the forks Running the forklift off a loading dock, ramp, or other surface we mishaps. All drivers must complete training and be evaluated before e-evaluated every 3 years. Re-training can be triggered by having an evations of unsafe operation. All employers must certify that each of a careful, safe manner. The loaded or empty terial as needed. The loaded of the mast. Falling loads.
Getting struck by the vehicle These accidents are caused by operator errors. Well trained drivers have very fee they re allowed to operate a fork-truck without direct supervision. They must be accident, near misses, re-assignment to different equipment or workplace, or obseints operators has been properly trained and is competent to operate the forklift in a Basic Forklift Operations: Do not allow anybody underneath raised forks, regardless whether forks at Handle only loads that are stable and safely arranged; secure palletized ma Do not handle loads in excess of the truck's or any attached component's and Always place forks under the load as far as possible when lifting; then state Do not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar which where you are going and keep a clear view. If the load obstructs you have drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed Always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stoppin When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for Stay within rated capacities of dock boards, bridge plates, or any other elements.	Falling from a platform on the forks Running the forklift off a loading dock, ramp, or other surface we mishaps. All drivers must complete training and be evaluated before e-evaluated every 3 years. Re-training can be triggered by having an evations of unsafe operation. All employers must certify that each of a careful, safe manner. The loaded or empty derial as needed. The analysis of the mast. Falling loads.
they're allowed to operate a fork-truck without direct supervision. They must be a accident, near misses, re-assignment to different equipment or workplace, or obse his operators has been properly trained and is competent to operate the forklift in a Basic Forklift Operations: Do not allow anybody underneath raised forks, regardless whether forks at Handle only loads that are stable and safely arranged; secure palletized material Do not handle loads in excess of the truck's or any attached component's at Always place forks under the load as far as possible when lifting; then stable Do not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar which where you are going and keep a clear view. If the load obstructs you have drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed Always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stopping. When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for Stay within rated capacities of dock boards, bridge plates, or any other elections.	e-evaluated every 3 years. Re-training can be triggered by having an evations of unsafe operation. All employers must certify that each of careful, safe manner. e loaded or empty terial as needed. atted capacity. ilize by slight rearward tilting of the mast.
Do not allow anybody underneath raised forks, regardless whether forks and Handle only loads that are stable and safely arranged; secure palletized made Do not handle loads in excess of the truck's or any attached component's not allways place forks under the load as far as possible when lifting; then stable Do not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk of Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar when where you are going and keep a clear view. If the load obstructs you never drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed Always keep to the right in 2-way traffic. No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stopping. When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for Stay within rated capacities of dock boards, bridge plates, or any other elements.	terial as needed. anted capacity. ilize by slight rearward tilting of the mast. falling loads.
Handle only loads that are stable and safely arranged; secure palletized ma Do not handle loads in excess of the truck's or any attached component's a Always place forks under the load as far as possible when lifting; then state Do not tilt mast forward unless setting the load down. Overhead and back guards must be in place to protect operator from risk o Use only safety platforms to lift people. When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar Watch where you are going and keep a clear view. If the load obstructs you Never drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed Always keep to the right in 2-way traffic No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stopping When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for stay within rated capacities of dock boards, bridge plates, or any other elections and them.	terial as needed. anted capacity. ilize by slight rearward tilting of the mast. falling loads.
When traveling in the forklift, follow these safety rules: Approval by a competent person is needed to operate equipment in a hazar Watch where you are going and keep a clear view. If the load obstructs you never drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed always keep to the right in 2-way traffic. No speeding; slow down on wet, slippery surfaces and when turning keep vehicle under control at all times to ensure and maintain safe stopping. When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting for Stay within rated capacities of dock boards, bridge plates, or any other elements.	dous location: most accidents occur while moving
Approval by a competent person is needed to operate equipment in a hazar Watch where you are going and keep a clear view. If the load obstructs you never drive up to anyone standing in front of fixed objects. No riders allowed unless vehicle is specifically designed for a passenger. When carrying a load, keep it as low as possible. Raise fork only as needed Always keep to the right in 2-way traffic. No speeding; slow down on wet, slippery surfaces and when turning Keep vehicle under control at all times to ensure and maintain safe stopping. When approaching or crossing obstructed vision locations, or blind spots, Be sure of sufficient clearances to overhead obstructions such as lighting if Stay within rated capacities of dock boards, bridge plates, or any other elections make sure structures are secure before driving on them.	dous location: most accidents occur while moving
 Stay within rated capacities of dock boards, bridge plates, or any other ele Always make sure structures are secure before driving on them. 	d to clear road surface g capability. slow down and sound the horn.
•	
and putterning.	
Conclusion: Never allow horseplay or stunt driving with a forklift; use good sense $Work\ Site\ R$	
Work-Site Hazards and Safety Suggestions:	
Personnel Safety Violations:	
Employee Signatures: (My signature attests and verifies m	y understanding of and agreement to comply with, all company safety policies of suffered, experienced, or sustained any recent job-related injury or illness.)

These guidelines do not supercede local, state, or federal regulations and must not be construed as a substitute for, or legal interpretation of, any OSHA regulations.