

Foreman/Supervisor's Signature:

Tailgate/Toolbox Safety Training



Company Name:		Job Site Location:
Date:	Start Time	Finish Time:Foreman/Supervisor:
		Topic 358: Safety for Road Brooms
industry. Road which can through to the of General vehice Employed regulation	d brooms are used to cow debris a considerable perator, co-workers, period requirements: ers must ensure that rooms regarding operation	reful piece of equipment for sealcoating, chip sealing, striping, and overlay work in the asphalt paving lean paved surfaces where debris pick-up is not necessary. Road brooms are quick, light machine le distance. Road brooms must be operated by a skilled and cautious operator to prevent accidents of destrians, and vehicle traffic. Following are guidelines for safe operation of road brooms: and broom operators are properly trained to safely operate the machine and are familiar with local son public thoroughfares, traffic control, and safety for pedestrian and vehicle traffic. It is personal protective equipment when operating road brooms, to include
eye prote Brooms All mace Road br	ection, respiratory prote must be equipped with hine parts which pose a noms must be inspecte	adequate roll-over protection and a seat belt. a hazard to personnel must be guarded. d before the start of work to ensure all guards are in place and secure. Check for any missing or loose alic oil, fuel, coolant, and oil leaks. Repair or replace any damaged parts before operation.
☑ Never p		vice, or maintenance while the engine is running. Use proper lockout/blockout-tagout
✓ Road br lights fo	ooms must be equipped r night or low light ope	with operating service, parking, and emergency brakes. Brake lights and operating rations are required.
	ooms must be equipped	ped with a manual audible warning device (horn) which can be heard over general job-site noise. I with a flashing warning light visible 360 degrees, for operation in traffic areas, or on any public
		and foot holds for mounting and dismounting the machine. Footholds must have a non-slip tread.
	r safe road broom op	
		achine unattended while the broom core is turning.
Any tool	s, equipment, or person	oroom has adequate seating and seat belts for passengers. nal items on the road broom must be secured to prevent movement while operating. Keep the d debris. Keep all controls free of oil, grease, or dirt.
■ Dust con	ntrol must be provided	when operations limit visibility, or dust becomes a hazard to traffic or personnel in the area. ward traffic or personnel during operation. If debris must be swept toward any pedestrian walkway
restrict p Image: Traffic of	pedestrian traffic from to control must be provide	he work area. Keep all broom operations an adequate distance from all personnel, ed any time operations encroach on a public thoroughfare. Flaggers must be used
🗵 Keep the		ol measures do not adequately control traffic. speed at all times. Lower gears and higher rpm allow the broom to do a more
☑ Do not f compart	<i>uel</i> the road broom wh ment or anywhere on th	ile the engine is running or hot. Do not allow fuel to overflow into the engine ne machine. Quickly clean or flush any spilled fuel.
		operated safely with proper training and common sense. Notify residents and commercial owners of unce and take appropriate measures to keep debris off other people's property and clean up after the
		Work Site Review
Specific Work	-Site Hazards and Safe	
Employee S	Signatures:	(My signature attests and verifies my understanding of and agreement to comply with, all company safety policies
		and regulations, and that I have not suffered, experienced, or sustained any recent job-related injury or illness.)